



**변류기(變流器)**

**YHBC-203D**

**BCT**

**전기적특성**

**ELECTRICAL CHARACTERISTICS**

최고회로전압(kV)	0.6	Highest voltage(kV)
주파수(Hz)	50/60	Frequency(Hz)
상용주파내전압(kV)	3	Power-frequency withstand voltage(kV)
충격내전압(kV) BIL	-	Lightning impulse voltage(kV). BIL
최대1차전류(A)	2000	Max. primary current(A)
2차전류(A)	5	Secondary current(A)

**기계적특성**

**MECHANICAL CHARACTERISTICS**

조임강도(Nm) M5/M6	2.8~3.5	TORQUE(Nm) M5/M6
중량(kg)	20	Approximate weight(kg)
기타 다른 사양은 문의 요망		Other specifications on request

**적용**

**SERVICES**

Metering			Protection		
Current Ratio	Class	VA	Current Ratio	Class	VA
600-400-300-200-100/5A	1.2	B-0.5(12.5VA)	600-400-300-200-100/5A	C200	50
2000-1000/5A			2000-1500-1200-800-400/5A		

※ Other specifications will be available on your request and contact with YOUNG-HWA directly.

※ For multi ratio transformers with tapings on the secondary winding, the accuracy requirements refer to the highest transformation ratio, unless otherwise specified.

2차 권선에 탭이 있는 다중비 변성기의 경우, 달리 규정하지 않는다면 비오차 요구사항은 변성기의 가장 높은 변성비에 적용된다.